

1

# METHOD TO INFER ENGINE COOLANT TEMPERATURE IN CYLINDER HEAD TEMPERATURE SENSOR EQUIPPED VEHICLES

## BACKGROUND OF THE INVENTION

### 1. Field of the Invention

The present invention relates generally to an automotive engine coolant temperature determination method. More particularly, the present invention relates to a method using a cylinder head temperature sensor to infer such a temperature.

### 2. Disclosure Information

It is well known that malfunctions of engine cooling systems, such as a leak, will generally cause damage to the engine due to excessive engine overheating. To indicate such an event, a temperature sensing system for an internal combustion engine may include an engine coolant temperature (ECT) sensor, a cylinder head temperature (CHT) sensor, or a combination of the two. The temperature sensors record a temperature and relay the information to an electronic engine controller, which, in turn, relays the information to an operator, typically via an instrument display panel.

In ECT sensor equipped vehicles the sensor typically communicates with a coolant passage in a cylinder head. The problem with ECT sensor equipped vehicles is that an accurate reading of the CHT can not be obtained. Having an accurate CHT reading is important with respect to fuel economy and emissions.

In CHT sensor equipped vehicles the sensor typically communicates with the cylinder head at a location adjacent the combustion chamber of the engine. A problem with CHT sensor equipped vehicles is that the ECT can not be accurately calculated. For example, the CHT can be up to 70 degrees Fahrenheit hotter than the ECT and the temperature gauge would read hot when the system is really operating within a normal temperature range, thereby giving a "false reading".

To combat these problems many vehicles are equipped with both ECT and CHT sensors. A problem with a two sensor system is that it is more costly than the single sensor systems. A further problem is that the algorithm programmed into the engine controller is more complex because of the need to receive information from two sensors.

It would therefore be desirable to provide a method of accurately inferring ECT in CHT sensor equipped vehicles that overcomes the deficiencies associated with previous systems.

## SUMMARY OF THE INVENTION

The present invention overcomes the disadvantages of the prior art approaches by providing a method of inferring ECT in CHT sensor equipped vehicles including the steps of measuring the CHT; calculating the ECT from the measured CHT as a function of at least one vehicle operational state, generating a signal for the calculated ECT, and sending the generated signal to a display.

It is an object and advantage of the present invention to calculate ECT as a function of the vehicle operational state. Calculation in this fashion prevents "false readings" which may arise when CHT is running hotter than ECT, but still within an acceptable operational range.

A feature of the present invention is to filter the calculated ECT to prevent inaccurate display readings resulting from sudden changes in vehicle operational states, the filter step being performed prior to the step of generating a signal.

2

These and other advantages, features and objects of the invention will become apparent from the drawings, detailed description and claims which follow.

## BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of an automotive vehicle according to the present invention;

FIG. 2 is a partial cross-sectional view of an internal combustion engine having a temperature sensing system according to the present invention; and

FIG. 3 is a flow chart showing a method for inferring ECT in CHT sensor equipped vehicles according to the present invention.

## DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring now to the drawings, FIG. 1 shows an automotive vehicle 10 having an internal combustion engine 12 and a dashboard 14 housing an instrument display panel 16. As known in the art, the display panel 16 has a variety of gauges which communicate various vehicle operational states such as vehicle speed, engine revolutions per minute, and engine temperature for example.

A temperature sensing system 11, shown in FIG. 2, infers ECT from a measured CHT. The engine 12 includes a cylinder block 18 having a cylinder 20 formed therein and a piston 22 reciprocally housed within the cylinder 20. A cylinder head 24 is mounted to the cylinder block 18, with a cylinder head gasket 26 disposed therebetween, such that the cylinder head 24 closes the outer end of the cylinder 20, thereby defining a combustion chamber 28 between the top of the piston 22 and an insulation deck 30 of the cylinder head 24. A sparkplug 32 is fastened to the cylinder head 24 to communicate with the combustion chamber 28. A cooling system 34 of the engine 12 is generally provided by a coolant passage 36 formed in the cylinder head 24. A coolant 38 circulates in coolant passage 36 to cool the engine 12.

According to the present invention, a temperature sensor 42 communicates with the insulation deck 30 in the cylinder head 24 adjacent the combustion chamber 28. Preferably, the temperature sensor 42 is a thermistor as is known in the art. The temperature sensor 42 senses the cylinder head 24 temperature and relays the information to an electronic engine controller (EEC) 44 having a keep alive memory (KAM) storage device 46.

Referring now to FIG. 3, according to the present invention, a method of inferring ECT from a CHT sensor is described. At step 50, the process is initiated. At step 52, it is determined whether a CHT is available from the EEC. If not, then at step 54 the engine temperature signal generated and sent to the display 16 (ECT DISPLAY) is set equal to a failure mode value of ECT (ECT FMEM). Generally, the engine temperature signal generated and sent to the display 16 at step 54 equals the combustion chamber air charge temperature during a cold start, and ramps to a calibratable constant whose value is typical for a warm engine.

If a valid CHT is available, then at step 56, it is determined whether the initial pass through this process has been completed (INIT FLG). The initial pass completed is indicated by a 1 as discussed below.

If the initial pass was completed, then at step 58, a temporary ECT value is determined. This temporary value is